



EN 60598 LED A+++ IK08 IP66 CE

Product description

- Corrosion resistant aluminum body
- Excellent heat dissipation for cooling electronics components
- Stainless steel screws
- Waterproof and durable silicone gaskets
- Chromate coating
- Electrostatic polyester powder coating
- Anchorage unit with galvanized
- Mechanical impact resistance IK08
- Protection grade IP66
- Electrical installation Class I

Lamp & Optics

- Poly Module ®
- Up to 140 lm/w
- 3000k-4000k-6500k
- 220-240v 50-60hz
- Beam angle: 30°, 60°, 90°, 150°, Asymmetric
- Cri > 80
- Options : DALI controllable

Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

	Power (W)	A	B	C	D	Anchor
LGT.10.106.01	36	3000	830	80	150	4xM12
LGT.10.106.02	36	4000	850	100	150	4xM14
LGT.10.106.03	72	5000	850	100	150	4xM16
LGT.10.106.04	72	6000	1100	100	200	4xM16
LGT.10.106.05	108	7000	1100	100	200	4xM18
LGT.10.106.06	144	8000	1350	100	200	4xM20

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
www.light34.com
export@light34.com