



EN 60598 LED A+++ IK08 IP66 CE

Product description

Corrosion resistant aluminum body
 Excellent heat dissipation for cooling electronics components
 Stainless steel screws
 Waterproof and durable silicone gaskets
 Chromate coating
 Electrostatic polyester powder coating
 Anchorage unit with galvanized
 Mechanical impact resistance IK08
 Protection grade IP66
 Electrical installation Class I

Lamp & Optics

Poly Module®
 Up to 140 lm/w
 3000k-4000k-6500k
 220-240v 50-60hz
 Beam angle: 30°, 60°, 90°, 150°, Asymmetric
 Cri > 80
 Options : DALI controllable

Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

	Power (W)	A	B	C	D	Anchor
LGT.10.107.01	36	4000	750	100	150	4xM14
LGT.10.107.02	72	5000	750	100	150	4xM14
LGT.10.107.03	72	6000	1000	100	200	4xM16
LGT.10.107.04	108	7000	1250	100	200	4xM16
LGT.10.107.05	144	8000	1500	100	200	4xM18

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
 Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
 Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
 www.light34.com
 export@light34.com