



EN 60598 LED A+++ IK08 IP66 CE

Product description

Corrosion resistant aluminum body
 Excellent heat dissipation for cooling electronics components
 Stainless steel screws
 Waterproof and durable silicone gaskets
 Chromate coating
 Electrostatic polyester powder coating
 Anchorage unit with galvanized
 Mechanical impact resistance IK08
 Protection grade IP66
 Electrical installation Class I

Lamp & Optics

Poly Module®
 Up to 140 lm/w
 3000k-4000k-6500k
 220-240v 50-60hz
 Beam angle: 30°, 60°, 90°, 150°, Asymmetric
 Cri > 80
 Options : DALI controllable

Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

	Power (W)	A	B	C	Anchor
LGT.30.103.01	10	500	200	125	4xM10
LGT.30.103.02	12	750	200	125	4xM10
LGT.30.103.03	14	1000	200	125	4xM10
LGT.30.103.04	20	1500	200	125	4xM10
LGT.30.103.05	24	2000	200	175	4xM12
LGT.30.103.06	28	2500	200	175	4xM12

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
 Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
 Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
 www.light34.com
 export@light34.com