

Product description

Corrosion resistant aluminum body
 Excellent heat dissipation for cooling electronics components
 Stainless steel screws
 Waterproof and durable silicone gaskets
 Chromate coating
 Electrostatic polyester powder coating
 Anchorage unit with galvanized
 Mechanical impact resistance IK08
 Protection grade IP66
 Electrical installation Class I


Lamp & Optics

Pluto-L®
 Driving current: 600mA
 2700k-3000k-3500k-4000k-6000k
 220-240v 50-60hz
 Beam angle: 18°, 25°, 45°
 Cri > 80
 Options : DALI controllable

Application

VELA is dedicated for urban illumination. Thanks to its adjustability in both horizontal and vertical directions, illuminating capability is very high. Main areas of usage are streets, squares, building surfaces, parks, statues etc.

	Power (W)	A	Driving Current
LGT.10.108.01	2x36	4000	600mA
LGT.10.107.02	3x36	5000	600mA
LGT.10.107.03	4x36	6000	600mA



We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
 Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
 Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
 www.light34.com
 export@light34.com