



EN 60598 LED A+++ IK08 IP66 CE

Product description

Corrosion resistant aluminum body
Acrylic diffuser
Stainless steel screws
Waterproof and durable silicone gaskets
Chromate coating
Electrostatic polyester powder coating
Anchorage unit with galvanized
Mechanical impact resistance IK08
Protection grade IP66
Electrical installation Class I

Lamp & Optics

Up to 100 lm/w
3000k-4000k-6500k
220-240v 50-60hz
Options : DALI controllable

Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

	Power (W)	A	B	C	Anchor
LGT.10.109.01	56	3000	1000	140	4xM12
LGT.10.109.02	56	3500	1000	140	4xM12
LGT.10.109.03	84	4000	1500	140	4xM14
LGT.10.109.04	84	4500	1500	140	4xM14
LGT.10.109.05	100	5000	2000	140	4xM16
LGT.10.109.06	100	6000	2000	140	4xM16

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
www.light34.com
export@light34.com