



EN 60598 LED A+++ IK08 IP66 CE

### Product description

Galvanized steel body  
Acrylic diffuser  
Stainless steel screws  
Waterproof and durable silicone gaskets  
Electrostatic polyester powder coating  
Anchorage unit with galvanized  
Mechanical impact resistance IK08  
Protection grade IP66  
Electrical installation Class I

### Lamp & Optics

Up to 140 lm/w  
3000k-4000k-6500k  
220-240v 50-60hz  
Options : DALI controllable

### Application

Light building elements are luminous design elements for public areas. They are particularly suitable for dividing and structuring outdoor spaces. They can be used to guide or lead people and vehicles. Their attention-drawing power is considerably greater than that of pole-top luminaires. Light building elements can be used to serve or highlight the architectural structure.

	Power (W)	A	B	Anchor
LGT.10.112.01	40	3750	500	4xM12
LGT.10.112.02	40	4000	500	4xM12
LGT.10.112.03	55	4500	500	4xM14
LGT.10.112.04	60	5000	500	4xM14

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.  
Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8  
Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11  
www.light34.com  
export@light34.com