



EN 60598 LED A+++ IK08 IP66 CE

Product description

Corrosion resistant aluminum body
Stainless steel screws
PMMA Acrylic diffuser
Chromate coating
Electrostatic polyester powder coating
Anchorage unit with galvanized
European Standards EN-60598
Mechanical impact resistance IK08
Protection Grade IP66
Electrical installation Class I

Lamp & Optics

Poly Module ®
Up to 140 lm/w
3000k-4000k-6500k
220-240v 50-60hz
Beam angle: 90°, 150°
Cri > 80
Options : DALI controllable

Application

Sophisticated and unique traditional design, robust and anti-corrosive structural performance of Pavonis Garden Lighting Pole will contribute to the long lifespan while illuminating the public areas such as gardens, parks, commercial outdoor zones. Its elegant lines and influential technical optical performance will meet any lighting requirements for custom made lighting projects. Ideal lighting solution for creating visual guidance with exceptional visual comfort using LED technology.

	Power (W)	A	B	C	Anchor
LGT.70.113.01	2 x 24	2500	1320	Ø 80	3 x M10
LGT.70.113.02	2 x 28	3000	1320	Ø 80	3 x M10
LGT.70.113.03	2 x 36	3500	1320	Ø 80	3 x M12

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
www.light34.com
export@light34.com