



EN 60598 LED A+++ IK08 IP66 CE

### Product description

Corrosion resistant aluminum body  
 Stainless steel screws  
 Sandblasted glass diffuser  
 Chromate coating  
 Electrostatic polyester powder coating  
 Anchorage unit with galvanized  
 European Standards EN-60598  
 Mechanical impact resistance IK08  
 Protection Grade IP66  
 Electrical installation Class I

### Lamp & Optics

Poly Module ®  
 Up to 140 lm/w  
 3000k-4000k-6500k  
 220-240v 50-60hz  
 Beam angle: 90°, 150°  
 Cri > 80  
 Options : DALI controllable

### Application

Carina Series Lighting Pole offers outdoor lighting defined by its unique traditional architectural design. Adjusted size and shape option for lighting pole body so that customers or lighting designers can integrate with any requirements, suitable for exterior lighting applications. Garden lamp post sharing a common approach to the redefinition of a classic design combined with advanced led lighting performance.

	Power (W)	A	B	C	Anchor
LGT.70.118.01	2 x 24	2500	1000	Ø 80	3 x M10
LGT.70.118.02	2 x 28	3000	1000	Ø 80	3 x M10
LGT.70.118.03	2 x 36	3500	1000	Ø 80	3 x M12

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.  
 Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8  
 Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11  
 www.light34.com  
 export@light34.com