



EN 60598 LED A+++ IK08 IP66 CE

Product description

Cast aluminum body
Stainless steel screws
Chromate coating
Electrostatic polyester powder coating
Sandblasted glass diffuser
Mechanical impact resistance IK08
Protection grade IP66
Electrical installation Class I

Lamp & Optics

Modo® Poly®
Up to 140 lm/w
3000k-4000k-6500k
220-240v 50-60hz
Beam angle: 150°
Cri > 80
Options : DALI controllable

Application

Traditional outdoor sconce lighting fixtures have many uses such as lighting the exterior of public and commercial buildings such as residential areas, retail buildings, hotels, hospitals, business center, shopping malls. Functionality and accent lighting can both provide by the sconce that leads the lighting effect you can decide. Wall-mounted lights illuminate around the building and, create safe and enlarge the usable area.

	Power (W)	A	B
LGT.90.100.01	14 W	600	1100
LGT.90.100.02	E 27	600	1100

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.
Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8
Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11
www.light34.com
export@light34.com