



EN 60598 LED A+++ IK08 IP66 CE

### Product description

Cast aluminum body  
Stainless steel screws  
Chromate coating  
Electrostatic polyester powder coating  
Acrylic diffuser, clear  
Mechanical impact resistance IK08  
Protection grade IP66  
Electrical installation Class I

### Lamp & Optics

Modo® Poly®  
Up to 140 lm/w  
3000k-4000k-6500k  
220-240v 50-60hz  
Beam angle: 150°  
Cri > 80  
Options : DALI controllable

### Application

Traditional outdoor sconce lighting fixtures have many uses such as lighting the exterior of public and commercial buildings such as residential areas, retail buildings, hotels, hospitals, business center, shopping malls. Functionality and accent lighting can both provide by the sconce that leads the lighting effect you can decide. Wall-mounted lights illuminate around the building and, create safe and enlarge the usable area.

	Power (W)	A	B
LGT.90.103.01	14	510	900
LGT.90.103.02	E 27	510	900

We reserve the right to make technical changes without prior notice.

LIGHT34 AYDINLATMA SAN. TIC. LTD.  
Ikitelli OSB Mutsan Sanayi Sitesi M8 Blok No:8  
Basaksehir | Istanbul | Turkey | 34490

+90 212 485 55 11  
www.light34.com  
export@light34.com