


	A	B	C	Power	Anchor
LGT.50.202.01	3000	600	100 x 150	28 W	4xM12
LGT.50.202.02	4000	750	100 x 150	36 W	4xM12
LGT.50.202.03	5000	1000	100 x 150	56 W	4xM16
LGT.50.202.04	6000	1000	100 x 200	72 W	4xM16
LGT.50.202.05	7000	1250	100 x 200	72 W	4xM16
LGT.50.202.06	8000	1250	100 x 200	108 W	4xM18

\* Dimensions are millimeter(mm)



### Product Description

- Corrosion resistant aluminium body
- Natural wood coating
- Very thin real teak tree
- Anchorage unit with galvanized
- Chromate conversion pretreatment
- Electrostatic powder coating
- Stainless steel screws (grade 304)
- Mechanical impact resistance IK08
- Protection Grade IP66
- Electrical installation Class I

### LED & Optics

- Up to 130 lm/w
- 3000K - 4000K - 6500K
- 220-240(V) 50-60(Hz)

### Options

- DALI controllable

### Color Options

- RAL 7016 Anthracite Grey
- RAL 9005 Black
- RAL 9006 White Aluminium
- RAL 7022 Umbra Grey
- RAL 9016 White
- RAL xxxx Optional